

P16HP

- 1" Hydraulic Hose
- Enerpac Pump
- Opening +20mm
- Dies: 10 12 14 16 19 23 27 31
- L*W*H: 330*400*270mm
- Weight: 25KG



P16HP

P20HP

- 1 1/2" 4SP Hydraulic Hose
- Enerpac Pump
- Opening +25mm
- Dies: 10 13 16 19 22 26 30 39 45
- L*W*H: 487*440*270mm
- Weight: 55 KG



P20HP

P16AP

- 1" Hydraulic Hose
- Enerpac Air Pump (FAST)
- Opening +20mm
- Dies: 10 12 14 16 19 23 27 31
- L*W*H: 400*400*270mm
- Weight: 28KG



P16AP

P20AP

- 1 1/2" 4SP Hydraulic Hose
- Enerpac Air Pump (FAST)
- Opening +25mm
- Dies: 10 13 16 19 22 26 30 39 45
- L*W*H: 487*440*270mm
- Weight: 55 KG



P20AP

P20D

- Digital Precision Control
- 1 1/2" 4SP Hydraulic Hose
- 110/220V 1PH; 380V/415V/440V 3PH
- Opening +25mm, Quick Change System
- Dies: 10 13 16 19 22 26 30 39 45
- L*W*H: 680*595*1330mm
- Weight: 177KG

Germany TUV-SUD CE Approved



P20D

P20Q

- 1 1/2" 4SP Hydraulic Hose
- 110/220V 1PH; 380V/415V/440V 3PH
- Opening +25mm, Quick Change System
- Dies: 10 13 16 19 22 26 30 39 45
- L*W*H: 595*440*650mm
- Weight: 177KG

Germany TUV-SUD CE Approved



P20Q

P32Q

- 2" 4SP Hydraulic Hose
- 110/220V 1PH; 380V/415V/440V 3PH
- Opening +32mm, Quick Change System
- Dies: 10 13 16 19 22 26 30 39 45 52 57 62 69
- L*W*H: 595*440*670mm
- Weight: 245KG

Germany TUV-SUD CE Approved



P32Q

P32D

- Digital Precision Control
- 2" 4SP Hydraulic Hose
- 110/220V 1PH; 380V/415V/440V 3PH
- Opening +32mm, Quick Change System
- Dies: 10 13 16 19 22 26 30 39 45 52 57 62 69
- L*W*H: 680*595*1395mm
- Weight: 245KG

Germany TUV-SUD CE Approved



P32D

PE58

- 2" 6SP Hydraulic Hose
- 4" Industrial Hose; Max 160mm Tube or Hose
- 110/220V 1PH; 380V/415V/440V 3PH
- Opening +50mm,
- Dies: 15 18 21 24 27 33 39 45 51 57 66
- Standard Quick Change System
- L*W*H: 730 x 483 x 812 mm
- Weight: 280 KG



PE58

P16CS 12/24V DC for Mobile Service

- Compact and Efficient
- Hydraulic Hose up to 1 inch
- Crimping Range: 4-45mm
- Opening: +20mm
- Diesets: 10 12 14 16 19 23 27 31
- Electric: 12/24V DC; 110/220/400V
- L*W*H: 450*300*550mm
- Weight: 70KG

P20CS P32CS available upon request



P16

S51Q

- Economical Crimping Machine
- 2" 4SP Hydraulic Hose
- 110/220V 1PH; 380V/415V/440V 3PH
- Opening +24mm, Quick Change System
- Dies: 15 18 21 24 27 33 39 45 51 57 66
- L*W*H: 610*440*690mm
- Weight: 260KG



S51Q

FP145 SIEMENS CONTROL

- 4" Industrial Hose, Max 160mm OD Tube or Hose
- 110/220V 1PH; 220V/380V/415V/440V/480V 3PH
- Opening +80mm, Quick Change System
- Dies: 15 18 21 24 27 33 39 45 51 57 66 84 92 100 108 116
- L*W*H: 950*1050*1650mm
- Weight: 1250KG



FP145

Various Speed Hose Reel

- Hose up to 2 inch
- Voltage single phase 230V
- Remote Control
- Max Load of reel: 500 KG
- L*W*H: 1200*1200*850mm
- Weight: 120KG



NC20 Nut Crimper

- Fitting size up to 1 1/4 inch
- Crimping Range: 4-65mm
- Opening: +20mm
- Master die length: 22 mm
- Motor: 4KW
- Crimpings per hour: 2200
- L*W*H: 685*1000*950 mm
- Weight: 320KG



NC20

FP120D

- Digital Precision Control
- Crimping range: 4-87mm
- Opening +65mm
- Quick change tool and die rack
- Dies: 10 13 16 19 22 26 30 39 45 52 57 62 69
- Voltage: 110/220V/400V/480V
- Motor: 5.5 KW
- L*W*H: 860*1050*1620 mm
- Weight: 1250 KG



FP120D

Pallet Test Bench PT1800/PT3600

- Pallet size: L*W*H: 1200*1200*1000mm
- Maximum Pressure 1800/3600 BAR
- Quick-filling option to 100 Liter/Min
- Precision Digital Control
- Reports Printing Option
- All parts by Maximator Germany
- L*W*H: 2500*1000*1850mm, 500KG



Hose Rack

- 7 Layer
- Max Load 800 KG
- L*W*H: 650*650*1900mm
- Weight: 70 KG
- Self Assembly



C300 Bench Top

- 2" Hose
- 2.2KW SIEMENS motor
- 300mm Blade
- L*W*H: 450*400*430mm
- Weight: 45KG



C300

C400 Standard

- 2" 4SP
- 3KW SIEMENS motor
- 250mm Blade
- L*W*H: 840x550x1150 mm
- Weight: 135KG



C400

Skiver 51

- mandrels 3/16"-2"
- internal skiving tools 5/8"-2"



Skiver 51M

- 1 external skiving tool
- mandrels 3/16"-2"
- internal skiving tools 5/8"-2"

