













■ Ordering Code

BS - **G** - **03** - **H** - **2B3B** - **N** - **D2** - **20**

Series No	Type of Mounting	Valve Size	Pressure Range	Vent Type	Type of Ele. Conduit	Coil Voltage	Design No
DG/DT 	G Subplate Mounting 	03: (3/8") ISO 6264-AS-06-2-A	B 7~70 bar 	2B2B 	N: DIN Type 	AC A1: AC110 A2: AC220	20 (G) DIN 912 bolts 
BG/BT 	T Threaded Connection 	06: (3/4") ISO 6264-AS-08-2-A	C 35~140 bar 	2B3B 	None:Box Type 	DC D1: DC12 D2: DC24	2090 (G) UNC bolts (North America) 
SBG/BRG 	HBG/HBT 	10: (1-1/4") ISO 6264-AT-10-2-A	H 70~250 bar 	2B2 	Y:Lead-Wire 	RAC R1: RAC110 R2: RAC220	20 (T) PT Connection 
DBG/DBT 	BSG/BST 	BSG-2P/SBSG 		3C3 			2090 (T) NPT Connection (North America) 

MODEL	DESCRIPTION	PAGE
DG-01	Remote Control Relief Valves(Sub-Plate Type)	248
DT-01	Remote Control Relief Valves(Threaded Type)	248
DG-02	Direct Type Relief Valves(Sub-Plate Type)	249
DT-02	Direct Type Relief Valves(Threaded Type)	249
BG-03-06-10	Pilot Operated Relief Valves(Sub-Plate Type)	250
BT-03-06-10	Pilot Operated Relief Valves(Threaded Type)	250
DBG-03	Pilot Operated Relief Valves(Sub-Plate Type)	251
DBT-03	Pilot Operated Relief Valves(Threaded Type)	251
HBG-03-06	Pilot Operated Relief Valves(Sub-Plate Type) High Pressure-315 bar	252
HBT-06	Pilot Operated Relief Valves(Threaded Type) High Pressure-315 bar	252
SBG-03-06-10	Low Noise Type Pilot Operated Relief Valves(Sub-Plate Type)	253
BRG-03-06-10	Back Valve(Sub-Plate Type)	253
BSG-03-06-10	Solenoid Controlled Relief Valves(Sub-Plate Type)	254
BST-03-06-10	Solenoid Controlled Relief Valves(Threaded Type)	254
BSG-03-06-10-2P	Solenoid Controlled Relief Valves-Dual Pressure (Sub-Plate Type)	255
SBSG-03-06-10	Low Noise Solenoid Controlled Relief Valves(Sub-Plate Type)	255